



XPOWER POWERPACK 1500 DATASHEET



IDEAL FOR POWER EMERGENCIES AND ALL RECREATIONAL ACTIVITIES

The XPower™ Powerpack 1500 is a backup power system that can supply up to 1500 W of household electricity and is an excellent alternative to a generator. It's quiet and has no fumes, fuel or moving parts, making it safe for indoor use. This mobile workhorse can also be used outdoors, and operates a wide variety of electronics including communication devices, power tools, full-size appliances and more.

The XPower™ Powerpack 1500 system consists of a battery pack that stores electricity, advanced electronics that convert 12 volts of DC power from the battery pack to household power, an AC power panel that contains two standard outlets, and a DC power panel that is used to operate 12 volt products. Combined in a rugged cart, the XPower Powerpack 1500 can be easily wheeled from room-to-room or outdoors over rough terrain.



High surge protection and automatic over-temperature and overload shutdown



Sealed, non-spillable 51 amp-hour AGM battery



Padded grip towing handle is removable for easy storage



Two three-prong AC outlets

APPLICATIONS:



www.xantrex.com
CUSTOMER CARE: 1.800.670.0707

Copyright © 2021 Xantrex LLC. All Rights Reserved. All trademarks are owned by Xantrex LLC.
V2. 11.12.2021



FRONT VIEW



DETACHABLE HANDLE

PRODUCT FEATURES

- Operates 120Vac or 12Vdc products anywhere
- Low voltage alarm and shutdown prevents deep battery discharge
- Battery level indicator confirms charge level
- High power 12Vdc connector
- Padded grip towing handle is removable for easy storage, and built-in side handles allow for easy lifting
- Sealed, non-spillable 51 amp-hour AGM battery
- High surge protection and automatic over-temperature and overload shutdown
- Two three-prong AC outlets

XPOWER POWERPACK 1500 DIMENSIONS



ELECTRICAL SPECIFICATIONS

POWERPACK 1500				
120Vac				
AC Output Power (continuous)	1350W			
AC Output Surge Capacity (peak)	3000W			
AC Output Voltage	120Vac			
AC Output Frequency	60Hz			
AC Output Waveform	Modified Sine Wave			
Inverter No-load Current	0.3A			
12Vdc				
Internal Battery Type	Sealed lead-acid, AGM			
Internal Battery Capacity	51Ah			
Internal Battery Voltage	12Vdc			
DC Power Socket (circuit breaker)	12A			
Charging System				
AC Charger Bulk Charging Current	5A			
Peak Charging Voltage	14.4Vdc			
Float Charge Voltage	13.6Vdc			
Charger Input Socket Current	12A			
Charging Times				
Battery Discharge Levels	100%	75%	50%	25%
Recharging Time from 120Vac (home)	24h	16h	11h	6.5h
Recharging Time from 12Vdc (vehicle)	6 – 8 hrs (100% discharge)			

GENERAL SPECIFICATIONS

POWERPACK 1500	
Product Weight (with handle)	53.5lb (24.3kg)
Product Dimensions (with handle) (H x W x L)	38 x 12.3 x 15.6" (965 x 313 x 395mm)
Product Dimensions (without handle) (H x W x L)	14.5 x 12.3 x 15.6" (370 x 313 x 395mm)
Part Number	802-1500

Specifications are subject to change without notice.

CONTACT

CUSTOMER SERVICE

1.800.670.0707
 customerservice@xantrex.com
Hours of operation:
 6:30am - 4:30pm PST, Monday to Friday



facebook.com/Xantrex



@Xantrex



youtube.com/XantrexTechnology

LEARN MORE ON:

www.xantrex.com